

FS-1100 SPECIFICATIONS

PRINTER SPECIFICATIONS

BASIC SPECIFICATIONS:

Configuration:	Small Workgroup Black & White Printer with 250 Sheet Drawer, Single Sheet Multi-Purpose Tray and Optional Network Card
Resolution:	Fine 1200 mode (1,200 x 1,200 dpi), Fast 1200 mode (1,800 x 600 dpi), 600 x 600 dpi, 300 x 300 dpi
Printer Memory:	Standard 32MB, upgradable to 544MB via 100 pin DDR DIMMs; Standard CF Card Slot (Type 1)
Electrical Requirements:	120V, 60Hz, 7.5A
Dimensions:	14.8"W x 15.5"D x 9.8"H
Weight:	22.1 lbs
Max Duty Cycle:	20,000 Pages Per Month

CONTROLLER SPECIFICATIONS:

Controller:	PowerPC405F5/360MHz
Supported PDL / Emulations:	PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), Diablo 630, IBM ProPrinter X24E, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL6/KPDL3, 1 Bitmap Font
Operating System Support:	Windows® 2000/XP/Vista; Mac OS 10.x; Linux
Connectivity / Interface:	Hi-Speed USB 2.0
KUIO LV Enhancement Slot:	Optional Network Interface (IB-23)
Network Support:	Please refer to IB-23 Section
Drivers:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers, Generic Driver for Windows Legacy
Utilities:	KM-NET Viewer, IC-Link, Status Monitor, PRESCRIBE Utilities

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Drawer, Single Sheet MPT
Drawer Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
MPT Paper Size:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio Custom (2.8" x 5.8" - 8.5" x 14.0")
Std/Max Paper Capacity:	251 Sheets/501 Sheets
Paper Weight:	16 - 32 lb Bond via Paper Drawer, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

OUTPUT SPEEDS:

Warm-Up Time:	Less than 15 Seconds (From Sleep Mode)
First Print Out:	Less than 6 Seconds (EcoFuser Off)
Pages Per Minute:	30 Letter, 24 Legal

PAPER HANDLING OPTIONS & ACCESSORIES:

PAPER DRAWER: PF-100

Paper Capacity:	250 Sheets
Maximum Drawers:	1
Paper Weight:	16 - 32 lb Bond
Paper Sizes:	LTR, LGL, Oficio2, A4, A5, B5, A6, Folio
Dimensions / Weight:	14.7"W x 15.4"D x 3.9"H / 7.7lbs or less

NETWORK INTERFACE CARD: IB-23

Interface:	KUIO LV
Supported Protocol:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Windows® Support:	Windows® 2000/XP/2003/Vista
Novell® Support:	Novell Netware® 5.x/6.x
Mac OS Support:	OS 9.x/10.x
UNIX OS Support:	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Network Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, NetBIOS over TCP/IP
Security Protocols:	IP Filtering, SSL/TLS (HTTPS), SNMP V2c/V3, IPv6, IEEE802.1x (EAP TLS/PEAP)
IPv6 Protocols:	HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMPv6
IPv4 Protocols:	HTTP, HTTPS, LPD, FTP, IPP, RawPort, ICMP, SMTP, POP3, SNMP, DNS, WINS, NetBIOS over TCP/IP, SNMP v1/v2c/v3, ThinPrint Compatible, Apple Bonjour Compatible
Utility:	KMnet Admin

ADDITIONAL MEMORY:

Available Memory:	64MB, 128MB, 256MB and 512MB DDR DIMMS
-------------------	----------------------------------------

CONSUMABLES:

Toner TK-142:	4,000 pages @ 5% Coverage
	Ships with 2,000 pages @ 5% Coverage, ISO 19752 Certified

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

Kyocera's ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today. Visit our TCO Tracker at www.kyoceramita.com and start saving.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks and trade names are the property of their respective owners. Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA ©2008 Kyocera Mita America, Inc. IC#855D400126



www.kyoceramita.com