

# FS-C5025N SPECIFICATIONS

## BASIC SPECIFICATIONS:

Configuration:	Color Tandem Network Printer with Standard 500 Sheet Drawer, 100 Sheet Multipurpose Tray, Optional Duplex, Additional Paper Drawers and Hard Disk Drive
Resolution:	600 x 600 DPI (Multi-bit)
Printer Memory:	Standard 128MB, Upgradeable to 640MB via 100 Pin DDR DIMMs, Standard CF Card Slot (Type 1) Optional Hard Disk Drive
Electrical Requirements:	120V, 60Hz, 9.1A
Dimensions:	13.6"W x 18.5"D x 15.2"H
Weight:	55.2 lbs
Max Duty Cycle:	85,000 Pages per Month

## CONTROLLER SPECIFICATIONS:

CPU/MHz:	Embedded PowerPC750CXr/500MHz
Supported PDL / Emulations:	PRESCRIBE, KPDL3 (PS3), PCL 6 (PCL 5c, PCL XL)
Fonts:	136 Fonts for KPDL3, 80 Outline Fonts for PCL 5c/XL, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100 BaseTX, Hi-Speed USB 2.0
KUIO LV Expansion Slot (1):	Optional IB-23 Secure Network Interface; Optional Printer Hard Disk Drive
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/Unix, Certified Uni Driver, Windows® 64-bit Drivers
Web Interface:	Kyocera Command Center
Utilities:	KM-NET Admin, KM-NET Viewer, KM-NET for Clients, PDF Direct Print, KM-NET for Accounting, PRESCRIBE Utilities

## OPTIONAL NETWORK INTERFACE: IB-23

Optional Network Interface supports IPv6, Security and Compliance	
Security Protocols:	SSL/TLS(HTTPS); SNMPv3

## PAPER SUPPLY:

Standard Paper Sources:	500 Sheet Drawer, 100 Sheet MPT
Drawer Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
MPT Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5 Custom: 2.8" x 5.4" - 8.5" x 14"
Std/Max Paper Capacity:	600/2,100 Sheets
Maximum Paper Sources:	Five
Paper Weight:	16 - 28 lb Bond via Paper Drawers, 16 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Cardstock, Postcards, Envelopes

## OUTPUT SPEEDS:

Warm-Up Time:	Within 75 Seconds
First Print Out Color:	13.0 Seconds
First Print Out Monochrome:	13.0 Seconds
Pages Per Minute (Color/Mono):	22/22 Letter, 20/20 A4, 18/18 Legal

## PAPER HANDLING OPTIONS:

### DUPLEX UNIT: DU-301

Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Paper Weight:	16 - 28 lb Bond
Dimensions / Weight:	13.6"W x 22"D x 9.7"H / 12.3 lbs

### PAPER DRAWER: PF-60

Paper Capacity:	500 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11", 8.5" x 14", A4, A5, B5
Dimensions/Weight:	13.6"W x 17.8"D x 4.1"H / 8.4 lbs

### ENVELOPE FEEDER: EF-310

Envelope Size:	Monarch; Commercial 6fl, 9, 10; International DL, C5
Paper Weight:	16 - 24 lb Bond
Stack Height:	1.5" or 40mm
Dimensions/Weight:	10.75"W x 7.01"D x 4.61"H / 1.65 lbs

### FACE-UP TRAY: PT-301

Paper Capacity:	250 Sheets for Printer, 100 Sheets for Duplexer (DU-301)
-----------------	---

## OPTIONS:

### HARD DISK DRIVE:

Enables Document Printing and e-MPS Functions: Private Print, Job Storage, Quick Copy Proof and Hold, Virtual MailBoxes
--

## CONSUMABLES:

TK-512K:	Black Toner* 8,000 Pages @ 5% Coverage*
TK-512Y:	Yellow Toner* 8,000 Pages @ 5% Coverage*
TK-512M:	Magenta Toner* 8,000 Pages @ 5% Coverage*
TK-512C:	Cyan Toner* 8,000 Pages @ 5% Coverage*

\* ships with 4,000 Pages @ 5% Coverage

Kyocera's objective is to manufacture superior products with the lowest Total Cost of Ownership (TCO), and have little or no impact on the environment. Kyocera's ECOSYS® Technology provides customers with a printing solution that incorporates life-long consumables and the lowest cost per print.

The operating costs of traditional cartridge-based page printers can easily exceed more than three times the original purchase price during the life of the product. By utilizing Kyocera's proprietary ECOSYS® Technology, a user can typically recoup a printer's purchase price in one year or less.



Document Solutions

Specifications and design are subject to change without notice.  
For the latest on connectivity visit [www.kyoceramita.com](http://www.kyoceramita.com).  
All trademarks and trade names are the property of their respective owners.  
Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,  
Fairfield, NJ 07004-0008, USA  
© 2006 Kyocera Mita America, Inc.  
Item Code # 85D400059



[www.kyoceramita.com](http://www.kyoceramita.com)