

KM-6030 Specifications

BASIC SPECIFICATIONS:

Configuration: Systems:	Enterprise/Workgroup Multifunctional with optional Print and Scan Standard 200 Sheet Dual Scan Document Processor, Duplex, 1,500 x 2 Sheet Letter Size Paper Decks, 525 x 2 Paper Drawers Plus 100 Sheet Multi-Purpose Tray, Optional Advanced Finishing and Paper Handling.
Resolution:	600 DPI. Interpolated 1800 x 600 DPI Resolution / 256 Levels, Fast 1200 Mode Print Resolution
Copier Memory:	Standard 128MB RAM, 40GB Hard Disk Drive
Magnification:	Full Size, 7 Reduction, 4 Enlargement Preset Ratios, Plus 25-400% Zoom
Electrical Requirements:	120V, 60Hz, 16A
Dimensions:	26.8"W x 30.9"D x 46.9"H
Weight:	415 lbs
Max Monthly Volume:	350,000 Pages Per Month

OUTPUT SPEEDS:

Warm-Up Time:	Within 30 Seconds, Program and Scan During Warmup, Auto Start
First Copy Out:	3.6 Seconds (Faceup)
First Print Out:	3.2 Seconds (Facedown)
Pages Per Minute:	60 Letter, 37 Legal, 31 Ledger

PAPER SUPPLY:

Standard Paper Sources:	1,500 x 2 Sheet Letter Size Paper Decks, Dual 525 Sheet Universal Paper Drawers, 100 Sheet MPT, Auto Selection / Switching, Add Paper While Running
Drawer Paper Size:	5.5" x 8.5" - 11" x 17"
MPT Paper Size:	5.5" x 8.5" - 11" x 17"
Std / Max Paper Capacity:	4,150 / 8,150
Paper Weight:	16 lb Bond - 90 lb Index via Paper Drawers, 13 lb Bond - 110 lb Index via MPT
Input Materials:	Bond Paper, Recycled Paper, Transparencies, Labels, Envelopes

DOCUMENT PROCESSOR:

Type:	Dual Scan Document Processor (DSDP)
Acceptable Originals:	5.5" x 8.5" - 11" x 17", Mixed Size Processing
Capacity:	200 Sheet DSDP / 80 Letter Size Originals Per Minute
Paper Weight:	13 - 43 lb Bond

DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	16 - 28 lb Bond
Duplex Modes:	Standard 1:2, 2:2, Book: 2, 2:1

COPY FUNCTIONS:

Imaging Modes:	Text, Photo, Text / Photo, Auto, Manual, ECO
Continuous Copy:	Up to 9,999, Auto Reset to 1
Additional Features:	Auto Center, Magnification and Paper Select, Batch Copy, Booklet Mode, Book Mode, Combine Image, Covers, Inserts, Erase Mode, Image Overlay, Image Rotate, Image Reverse, Interrupt, Job Build, 9 Job Reserves, Job Queue, Margin Shift, Mirror Image, Memo Mode, Modify Copy, Proof Copy, Page Numbering, Transparency Mode, Job Time Information, 1,000 Management Codes, XY Zoom, 3 Shortcut Keys Document Management: Store Documents, File Merge, Forms Composition, Repeat Copy

PAPER HANDLING OPTIONS:

PAPER DECK: PF-650

Paper Capacity:	4,000 Sheets
Paper Weight:	17 lb Bond - 90 lb Index
Paper Size:	8.5" x 11"
Dimensions / Weight:	14.6"W x 23.2"D x 27.3"H / 90.4 lbs

PAPER DECK: PF-660

Paper Capacity:	4,000 Sheets
Paper Weight:	17 lb Bond - 110 lb Index
Paper Size:	8.5" x 11", 8.5" x 14", 11" x 7"
Dimensions / Weight:	26.4"W x 22.8"D x 27.7"H / 99.2 lbs

MULTI-FUNCTIONAL FINISHER: DF-650

Stack Capacity:	Main Tray: 3,000 Sheets; Sub Tray: 200 Sheets
Paper Size:	Main: 8.5" x 11" - 11" x 17"; Sub: 5.5" x 8.5" - 11" x 17"
Paper Weight:	12 lb Bond - 110 lb Index
Staple Capacity:	50 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"
Edge Staple Position:	4 Positions: Top Left, Bottom Left, Left Side, Center
Saddle Stitch:	8.5" x 11" - 11" x 17"; Up to 16 Sheets
Dimensions / Weight:	31.4"W x 25.2"D x 43.3"H / 161 lbs

MULTI TRAY: MT-1

Number of Trays:	5
Capacity:	150 Sheets (8.5" x 11") Per Tray
Paper Size:	5.5" x 8.5" - 11" x 17"
Paper Weight:	12 lb Bond - 90 lb Index
Dimensions / Weight:	14.5"W x 15.5"D x 22.6"H / 33 lbs

BOOKLET FOLDER: BF-1

Folding Capacity:	1 - 16 Sheets
Capacity:	1 - 5 Sheets - 30 Booklets; 6 - 10 Sheets - 20 Booklets; 11 - 16 Sheets - 10 Booklets
Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	16 lb Bond - 110 lb Index, Over 20 lb is one sheet only
Dimensions / Weight:	23.3"W x 17"D x 10"H / 42 lbs

PUNCH UNIT: PH-4

Paper Size:	8.5" x 11" - 11" x 17"
Paper Weight:	12 lb Bond - 110 lb Index
Number of Holes:	2 and 3
Weight:	7 lbs

CONNECTIVITY OPTIONS:

PRINT: PRINT SYSTEM (V)

Controller:	Embedded PowerPC750 / 600 MHz Controller
Printer Memory:	Standard 64MB, Upgradeable to 576MB via 100 Pin DIMMS, Optional e-MPS Printer HDD, Standard CF Card Slot (Type 1)
Supported PDL/Emulations:	PRESCRIBE, PCL6 (PCL XL, PCL 5e), KPDL3 (PS3), KGGL (HP-GL/2), Diablo 630, IBM ProPrinter X24, Epson LQ850, Line Printer
Fonts:	80 Outline Fonts for PCL XL/5e, 136 Outline Fonts for KPDL3, 1 Bitmap Font
Windows® OS Compatibility:	Windows® 95/98/Me/NT4.x/2000/XP/2003
Novell® OS Compatibility:	Novell NetWare® 3.x/4.x/5.x/6.x
Mac OS Compatibility:	OS 8.x/9.x/10.x
UNIX OS Compatibility:	Sun OS 4.1.x; Solaris 2.x; AIX, HP-UX (LPR)
Connectivity / Interface:	Standard 10/100BaseTX, High Speed USB 2.0, Parallel IEEE1284
KU10 LV Expansion Slots (2):	Optional e-MPS Hard Disk Drive Optional 1B-23 Secure NIC
Supported Protocols:	TCP/IP, IPX/SPX, AppleTalk, NetBEUI
Driver:	KX Driver for Windows®, PPD for Mac, PPD for Linux/UNIX, Certified Uni Driver, Windows® 64-bit Drivers
Utilities:	KM-NET Viewer, PDF Direct Print, KX Spool Center, KM-NET for Clients, KM-NET Printer Disk Manager, Network Advanced Setup Utilities, PRESCRIBE Utilities

E-MPS HARD DISK DRIVE: HD-10

Enables e-MPS Functions:	Private Print, Job Storage, Quick Copy, Proof and Hold, Virtual MailBoxes
--------------------------	---

NETWORK SCANNING: SCAN SYSTEM (G)

Resolution:	200, 300, 400, 600 DPI
Scan Speed:	Up to 80 Sheets Per Minute
File Formats:	PDF, TIFF
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP
Scanning Features:	KM Document Flow System - Document Management System, Scan to PC/File, Scan to Mac, Scan to E-Mail, Scan to FTP, TWAIN
Driver:	TWAIN Driver, TWAIN Driver for Mac
Utilities:	KM DB-Assistant, KM Scanner File Utility, Scan to Mac Utility, KM Scanner Address Book, Address Book Editor, LDAP Converter Utility, Network Advanced Setup Utilities

DATA SECURITY KIT: DATA SECURITY KIT (B)

Provides security overwrite for automatic and manual deletion of copy and print data

ADDITIONAL OPTIONS:

iTag Document Solution; KYOCERA; 32/64/128/256MB DIMMS for Print System



Common Criteria Validated EAL3
Data Security Kit (B) Software V1.10E

* This validation for information security that this product earned indicates that it conforms with security assurance requirements as a result of evaluations based on specific evaluation criteria and evaluation standards.



Specifications and design are subject to change without notice.
For the latest on connectivity visit www.kyoceramita.com.
All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, PO Box 40008,
Fairfield, NJ 07004-0008, USA
©2006 Kyocera Mita America, Inc.



www.kyoceramita.com