

KM-F1060 Specifications

BASIC SPECIFICATIONS:

Configuration:	High Volume Desktop Facsimile with a 33.6Kbps Modem, Standard 100 Sheet Document Processor, 250 Sheet Paper Cassette and Single Sheet Bypass, Standard GDI Printing, Optional Network Scan/IFax, Optional G3 Dual Line Expansion, Optional 550 Sheet Paper Cassette.		
Compatibility:	ITU-T Group 3, ECM		
Scanning Resolution:	Standard:	203 dpi x 98 lpi	
	Fine:	203 dpi x 196 lpi	
	Super Fine:	406 dpi x 391 lpi	
	High Resolution:	600 x 600 dpi	
Print Resolution:	Fax/Copy:	600 x 600 dpi	
	Print:	600 x 600 dpi, 300 x 300 dpi	
Fax Memory (Std/Max):	12MB/512MB		
Memory Capacity (Std/Max):	720 pages/12,750 pages		
Document Memory Backup:	Flash Memory		
Coding System:	MH/MR/MMR/JBIG		
Scanning Method:	Contact Image Sensor (CIS)		
Print Method:	Monochrome Laser		
Print Width (Max):	8.15"		
Electrical Requirements:	120V, 50/60Hz		
Dimensions:	17.7"W x 16.5"D x 17.6"H		
Weight:	48.5 lbs		

OUTPUT SPEEDS:

Modem Speed:	33.6Kbps w/ Auto Fallback
Transmission Speed:	Approximately 2.7 Seconds per Page
Pages Per Minute:	19 Letter

PAPER SUPPLY:

Standard Paper Sources:	250 Sheet Cassette, Single Sheet Bypass
Drawer Paper Size:	8.5" x 11", 8.5" x 14"
Bypass Paper Size:	5.5" x 8.5", 8.5" x 11", 8.5" x 14"
Paper Capacity (Std/Max):	250 / 800
Paper Weight:	16-28 lb Bond
Output Capacity:	150 Sheets

DOCUMENT PROCESSOR:

Type:	Automatic Document Feeder (ADF)	
Acceptable Originals:	5.5" x 5.5" - 8.5" x 14"	
Capacity:	100 Sheet ADF	
Paper Weight:	14 - 28 lb Bond	
Effective Scanning Width:	8.34"	
Quick Scan Speed:	Standard:	0.7 Seconds
	Fine:	1.4 Seconds
	Super Fine:	2.8 Seconds

DUPLEX UNIT:

Paper Size:	5.5" x 8.5" - 8.5" x 14"
Paper Weight:	20 - 24 lb Bond

FAX FUNCTION:

DIALING CAPABILITIES:

One Touch Dialing Keys:	80
Program Keys:	80
Speed Dialing Codes (Std/Max):	200/920
Total Numbers Stored (Std/Max):	280/1,000
Group Dialing:	80
Other Dialing:	Auto Dial, Intelligent Redial, Automatic Redial, Last Number Redial, Directory Search Dial, Chain Dial, Alternative Number Dial, Pulse/Tone Dial, Off Hook Dial
Max Dialing Digits:	36

ADDITIONAL FAX FEATURES:

Driver:	PC Fax Driver (Network Fax requires IF-47 Scanner Kit)
Transmission/Reception:	Multi Access, Memory Transmission, Quick Memory Transmission, Deferred Transmission, Priority Direct Transmission, Job Reservation (Sending/Receiving), Batch Transmission, Multi-Station Transmission, Relay Transmission (SMTP), Auto Fax/Tel Switching, Polling, Continuous Polling, Deferred Polling, Substitute Reception, Memory Reception, Fax Forwarding, Broadcasting, Auto Reduction, Fixed Reduction, Verification Stamp, Duplex Reception, Distinctive Ring Detection (DRD)
Security Communication/Codes:	Fax Access Code (Fax Lock), Pin Code Access, Sub-Address Transmission, Department Code Access (50)
Journals/Lists:	Transaction Journal, Communication Journal w/Image, Directory Sheet, Department Code List, Auto Dial List, Fax Parameter List, Communication Reserve Report
Utilities:	Network Address Book Editor, PC Fax Software, Device Configuration Editor

COPY FUNCTION:

Continuous Copy:	Up to 999
Reduction/Enlargement:	71% - 141%
Additional Features:	Duplex Copy, Electronic Sort, Rotate Copy

CONNECTIVITY

STANDARD PRINT:

Print Memory :	32MB
Windows® OS Compatibility:	Windows® 98/Me/NT4.x/2000/XP
Connectivity / Interface:	Standard 10/100BaseTX, USB 1.1
Supported Protocol:	TCP/IP
Supported PDL/Emulations:	Windows® GDI
Print Resolution:	600 x 600 dpi
Driver:	GDI Driver for Windows®
Utilities:	Status Monitor
Additional Features:	Duplex Print, N-Up Printing, Scaling, Confidential Mailbox Printing (requires optional 256MB or 512MB SD Memory Card)

NETWORK SCAN/IFAX: IF-47 Scanner Kit

SCAN:

Type:	Monochrome Network Scanner
Resolution:	600 x 600 dpi, 300 x 300 dpi, 150 x 150 dpi
File Formats:	PDF, TIFF
Scan Speed:	1.1 Seconds per Page (150 x 150 dpi)
Connectivity:	Standard 10/100BaseTX
Scanning Features:	Scan to PC, Scan to E-Mail, Scan to FTP
Supported Protocols:	TCP/IP, SMTP, POP3, MIME, DHCP, LDAP, SNMP/MIB
Utilities:	Document Manager, Document Viewer
Additional Features:	LDAP, File Name Entry

INTERNET FAX:

IFax Compatibility:	ITU-T T.37, IETF RFC 2305
Connectivity:	Standard 10/100BaseTX
Supported Protocols:	TCP/IP, SMTP, POP3, MIME
File Formats:	TIFF-FX

PAPER HANDLING OPTION:

PAPER DRAWER: PF-47

Paper Capacity:	550 Sheets
Paper Weight:	16 - 28 lb Bond
Paper Size:	8.5" x 11" - 8.5" x 14"
Dimensions:	17.7"W x 17.9"D x 5.5"H

ADDITIONAL OPTIONS:

G3 Multi-Fax Board (MP-47) for Dual Line Fax, Handset (HS-47), Stand

CONSUMABLES: TD-47

TK-47:	All-in-One Cartridge 5,000 Pages@ 5% Coverage*
	* based on ITU-T No. 1 Chart in Standard Mode
	KM-F1060 ships with one (1) full TD-47 Cartridge

The KM-F1060's new QWERTY style keyboard makes document-sending via Fax, Scan or IFax quick and efficient.



Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks and registered trademarks are the property of their respective manufacturers.

Kyocera Mita America, Inc. Headquarters:
225 Sand Road, PO Box 40008, Fairfield, NJ 07004-0008, USA
© 2005 Kyocera Mita America, Inc.



www.kyoceramita.com