

Triumph®

PAPER CUTTERS

→ 721-06 LT PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: front safety light beams; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | high storage capacity, programmable back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements | up to 9 repeat cuts can be integrated into a program in a single step | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut, eject (with and without program mode), and memory functions as well as a delete and insert mode for modifying program steps | automatic measuring correction in case of back gauge displacement | "set" function key for reference measurement | self-diagnostic system with error indication on display | integrated calculator | push buttons for fast back gauge movement (forward and reverse) | electric blade and back gauge drive | HSS Solingen steel blade | precision swing-cut blade movement | solid steel blade carrier and adjustable blade guides | hydraulic clamp drive | clamp pressure is fully adjustable between 550 and 4,400 psi | false clamp and foot pedal for pre-clamping | spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | durable stainless steel work surface, front and rear | air jets on front and rear tables allow easy movement of paper | all-metal construction | optional side tables with stainless steel surface extend work area

Dimensions (D x W x H): 59 1/2 x 51 3/8 x 52 1/2 inches (82 3/4" W with side tables), Shipping weight: 1,686 lbs. (1,772 with side tables).



CONTROL MODULE




The back gauge control module has a digital display and keypad for programming.

SIDE TABLES / LIGHT BEAMS



Optional side tables extend the working surface. Safety light beams are standard.

TABLE AIR JETS



Air jets on front and rear tables allow easy movement of paper.

→ TRIUMPH 721-06 LT

Cutting width	28"
Cutting height	3"
Narrow cut	3/4"*
Cutting length behind blade	28 7/8"
Table length in front of blade	20 7/8"
Motor	2 hp
Power supply	220 V, 3 phase

* 3 1/2" with false clamp

Dealer:

MBM
CORPORATION

3134 Industry Drive
North Charleston, South Carolina 29418
800-223-2508, fax: 843-552-2974
www.mbmcorp.com

IDEAL.MBM
CORPORATION

1675 Sismet Road, unit 4
Mississauga, Ontario L4W 4K8
800-387-2528, fax: 905-840-1114
www.ideal-mbm.com