

# Triumph®

PAPER CUTTERS

## → 5222 DIGICUT PROGRAMMABLE HYDRAULIC CUTTER

"SCS" (Safety Cutting System) package: front safety light beams; transparent safety cover on rear table; main switch and safety lock with key; electronically controlled, true two-hand operation; 24 volt controls (low voltage); patented IDEAL safety drive; automatic blade return from every position; automatic clamp return from every position; disc brake for instant blade stop; blade and cutting stick can be changed without removing covers; blade changing device covers cutting edge of blade; blade depth adjustment from outside of machine | high storage capacity, programmable "EP" back gauge control module with 10 button keypad and LED display stores 99 programs (up to 99 steps each) and frequently used measurements | up to 9 repeat cuts can be integrated into a program in a single step | digital measurement readout in cm or inches (accurate to 1/10 mm or 1/100 inch) | control module features repeat cut and eject functions | "set" function key for reference measurement | self-diagnostic system with error indication on display | electric blade and back gauge drive | Solingen steel blade | solid steel blade carrier and adjustable blade guides | hydraulic clamp drive | clamp is guided on both sides to apply even pressure along entire cutting width and is fully adjustable between 440 and 2,420 psi (ideal for digital printing) | false clamp and foot pedal for pre-clamping | dual side guides on front and rear tables | electric, spindle-guided back gauge with narrow separations and plastic gliders | electronic hand wheel with variable speed control for manual back gauge setting | bright, LED optical cutting line | standard side tables extend work area | all-metal construction

Dimensions (D x W x H): 43 x 65 x 51 1/2 inches. Shipping weight: 900 lbs.



### "EP" CONTROL MODULE



The "EP" back gauge control module stores 99 programs and frequently used measurements.

### SAFETY LIGHT BEAMS



Safety light beams protect the operator and allow back gauge to automatically advance to the next cut.

### → TRIUMPH 5222 DIGICUT

Cutting width	20 1/2"
Cutting height	3 1/8"
Narrow cut	7/8"*
Cutting length behind blade	20 3/8"
Table length in front of blade	16"
Motor	2 hp
Power supply	115 V, 60 Hz**

\* 3 1/2" with false clamp

\*\* 20 amp dedicated line required

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
www.mbmcorp.com

**IDEAL.MBM**  
CORPORATION

1675 Sismet Road, unit 4  
Mississauga, Ontario L4W 4K8  
800-387-2528, fax: 905-840-1114  
www.ideal-mbm.com