

## ➔ 352S PROFESSIONAL SERIES AIR SUCTION FOLDER

air suction feed system, suitable for coated stocks | adjusts in seconds for standard and custom folds | variable speed control | powered exit conveyor | bottom-feed, top-loading design for continuous reloading and dependable sheet separation | polyurethane foam rollers eliminate the need for fold roller pressure settings | turbine blower fully enclosed for quiet operation | 2 fold plates | heavy-duty, non-flexing side frames | needle bearings for high speed production | mounted on casters | optional extended delivery system, crossfold for right-angle folding, and slitting, scoring, and perforating attachments

Dimensions (D x W x H): 22 ¼ x 51 ¼ x 43 ½ inches, Shipping weight: 312 lbs.



### ENCLOSED TURBINE BLOWER



The low-maintenance blower does not require filter changes.

### TOP-LOADING PAPER FEED



A top-loading paper feed system allows continuous operation.

### ➔ 352S

Speed	30,000 sheets/hr*
Paper size	3 ¾" x 4 ¾" to 12 ½" x 17 ¾"
Paper weight	13 to 110 lbs.*
Sheet capacity	450*
Power supply	115 V, 60 Hz

\* may vary due to variations in paper and power supply

Dealer:

**MBM**  
CORPORATION

3134 Industry Drive  
North Charleston, South Carolina 29418  
800-223-2508, fax: 843-552-2974  
www.mbmcorp.com

**IDEAL.MBM**  
CORPORATION

1675 Sismet Road, unit 4  
Mississauga, Ontario L4W 4K8  
800-387-2528, fax: 905-840-1114  
www.ideal-mbm.com